

DINGLI
ORDER PICKER
PUSH AROUND



DINGLI ORDER PICKER PUSH AROUND



Model	DYT 2-2.7S	DYT 2-3.7SW	DYT 2-4.5S
S.W.L	300kg	300kg	300kg
Max. Occupants	1	1	1
Max. Working Height A	4.70m	5.70m	6.50m
Max. Platform Height B	2.70m	3.70m	4.50m
Overall Length C	1.38 m	1.38m	1.42m
Overall Width D	1.06 m	1.06m	1.08m
Overall Height E	1.89 m	2.39m	2.28m
Platform Size (Length×Width)	0.64m×0.80m	0.64m×0.80m	0.64m×0.80m
Ground Clearance	0.08m	0.08m	0.08m
Wheelbase	0.92m	0.92m	0.95m
Lifting Motor	12VDC/1.6kW	12VDC/1.6kW	12VDC/1.6kW
Up/Down Speed	22/12sec	33/18sec	30/17sec
Max. Working Slope	1°	1°	1°
Batteries	2×12V/85Ah	2×12V/85Ah	2×12V/85Ah
Integrated Charger	12V/30A	12V/30A	12V/30A
Tyres (Front Wheels)	6in	6in	6in
Tyres (Back Wheels)	Φ152×55mm	Φ152×55mm	Φ152×55mm
Weight	460kg	490kg	605kg

Standard Equipment

- Emergency Lowering System
- Battery Charge Indicator
- Two Brakes And Two Brake Pads
- Voltage Indicator
- Safety Bracket
- Drawal Type Battery Box
- Emergency Stop Button
- All Motion Alarm
- Flashing Beacon
- Flat Platform
- Cylinder Holding Valve
- Tilt Sensor With Alarm
- Onboard Diagnostic System
- Overload Sensor With Alarm

