

DINGLI

LEO 23T

SPIDER LIFT-CRAWLER

DINGLI[®]
Exceed · New Height

LEO 23T

PERFORMANCE

Working height, max.	23.20 m
Platform height, max.	21.20 m
Horizontal outreach, max. (250 kg)	12.50 m
Horizontal outreach, max. (80 kg)	15.60 m
Platform capacity, max.	250 kg
Jib, movable	180 °
Platform, rotatable	180 °
Turntable rotation, max.	450 °
To be jacked up on ground slope of	16.7 ° / 30.0 %
Track drive, height- and width-adjustable	19 / 46 cm
Gradeability, max.	16.7 ° / 30.0 %
Slope angle, max.	19.0 ° / 34.0 %
Travel speed, max.	4.0 km/h

MEASUREMENTS*

Platform (height) (A)	1.10 m
Platform (length) (B)	1.20 m
Platform (width) (C)	0.80 m
Length (D)	6.20 m
Length without platform (E)	6.20 m
Height (F)	1.99 m
Width, min. (G)	0.99 m
Ground clearance, max. (H)	0.42 m
Track (length x width) (I)	1.45 x 0.20 m
Outrigger footprint both side wide (length) (J)	4.70 m
Outrigger footprint both side wide (width) (K)	4.70 m
Outrigger footprint one side narrow (length) (L)	6.30 m
Outrigger footprint one side narrow (width) (M)	3.65 m
Outrigger footprint both sides narrow (width) (N)	2.65 m
Outrigger plate Ø	0.18 m

WEIGHT*

Total weight	3050 kg
Live load in travelling position	3.90 kN/m ²
Live load in working position	1.60 kN/m ²
Point load per outrigger plate, max.	23.70 kN

POWER SOURCES

Standard power sources:

Electric motor	(country-specific 1-phase)
Combustion engine (Diesel)	Kubota Z602 (10.8 kW / 14.5 hp)
Fuel tank capacity (Diesel engine)	25.0 l

POWER SUPPLY

Electric current, max. country-specific, on request

STANDARDS

Harmonised standard DIN EN 280:2016

LEO 23T

