

SLM-300E

SELF-PROPELLED SCISSOR LIFT - ELECTRIC



Standard Configuration

- Proportional control
- Automatic brake system
- Pothole protection
- Emergency stop button
- Fault diagnosis system
- Tilt protection system
- No marking tyre
- Buzzer
- 4*2 drive

Optional Configuration

- Optional Configurations
- AC power and airway tube to the platform
- Working light on the platform.



SLM-300E

SELF-PROPELLED SCISSOR LIFT - ELECTRIC



Model	BM-SLM300E	BM-SLM300E
Max. working height	5m	5.9m
Max. platform height	3m	3.9m
Platform (L x W)	1.15m x 0.6m	1.15m x 0.6m
Extension deck size (L x W)	1.15m x 0.7m	1.15m x 0.7m
Extension deck (Roll out)	0.55m	0.55m
Overall length (Stowed)	1.32m	1.32m
Overall width (Stowed)	0.76m	0.76m
Overall height (Rails up)	1.86m	1.94m
Overall height (Rails down)	1.5m	1.59m
Ground clearance (Stowed)	0.05m	0.05m
Wheelbase	1.0m	1.0m
Weight	620kg	645kg
Max. gradeability	25%	25%
Turning radius (Inside)	0.4m	0.4m
Turning Radius (Outside)	1.35m	1.35m
Lift/lowe time	30S/20S	30S/20S
Travel speed (Stowed)	3.5km/h	3.5km/h
Travel speed (Raised)	1.0km/h	1.0km/h
Platform capacity (SWL)	240kg	240kg
SWL of extension deck	100kg	100kg
Max. no of person	1	1
Max. operating slope	1.5°/2°	1.5°/2°
Lift/drive motor	0.8kW/DC24V	0.8kW/DC24V
Power source	2 x 12V/80Ah	2 x 12V/80Ah
Charger	24V/12A	24V/12A
Tire size	Ø0.23 x 0.08m	Ø0.23 x 0.08m




Chassis Drawer



Emergency Descend Valve



Pedal Lock



Warning Light



Platform Control



Traceless Tires



Delivering Safety & Productivity

Chennai | Bengaluru | Mumbai | Ahmedabad | Delhi | Kolkata | Sri Lanka | Qatar

equipment@mtandt.com

90901 01065

www.mtandt.com