

DINGLI

JCPT1218RT

SELF PROPELLED SCISSOR LIFT - DIESEL



Standard Equipment

- Proportional controls
- Self-lock gate on platform
- Drivable at full height
- Foam-filled tyre
- 4WD
- Automatic brakes system
- Swing-out engine tray
- Emergency lowering system
- Emergency stop button
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- Anti-restart engine protection
- All Motion Alarm
- Horn
- Hour meter
- Safety brackets
- Folding guardrails
- European III emission engine
- Flashing Beacon
- Hydraulic oil cooler
- Oscillating Axle
- Extended Platform
- Forklift pockets

Options

- Overload sensor with alarm
- Automatic leveling hydraulic outriggers
- AC power to platform
- Platform work lights
- Hydraulic generator
- Hydraulic water pump
- Non marking tyres



DINGLI

JCPT1218RT

SELF PROPELLED SCISSOR LIFT - DIESEL

Size	JCPT1418RT	JCPT1218RT
Max. Working Height (A)	14.30m	12.00m
Max. Platform Height (B)	12.30m	10.00m
Overall Length (With/Without Outriggers) (C)	3.84m/3.19m	3.84m/3.19m
Overall Width (D)	1.76m	1.76m
Overall Height (Rails Up)	2.74m	2.59m
Overall Height (Rails Down) (E)	1.97m	1.82m
Platform Size (Lenth/Width) (F)	2.88m×1.52m	2.88m×1.52m
Platform Extension Size (G)	1.43m	1.43m
Ground Clearance	0.24m	0.24m
Wheel Base (H)	2.29m	2.29m
S.W.L	363kg	454kg
S.W.L On Extension	136kg	136kg
Max. Occupants	3	4
Turning Radius (Inside/Outside)	2.15m/4.85m	2.15m/4.85m
Travel Speed (Stowed)	5.20km/h	5.20km/h
Travel Speed (Raised)	0.48km/h	0.48km/h
Up/Down Speed	45/46sec	38/46sec
Gradeability	40%	40%
Max. Working Slope	2°/3°	2°/3°
Tyre	26×12-16.5	26×12-16.5
Engine Kubota D1105	18.6kw/2400rpm	18.6kw/2400rpm
Hydraulic Tank	71L	71L
Diesel Tank	47L	47L
Overall Weight (With/with Outriggers)	5050kg/5050kg	4300kg/3900kg

