

**DINGLI**

# JCPT1523RT

**SELF PROPELLED SCISSOR LIFT - DIESEL**



## Standard Equipment

- Proportional controls
- Self-lock gate on platform
- 4WD
- Automatic brake system
- Slide-out engine tray
- Safety electric pump
- Emergency stop button
- Cylinder holding valve
- Onboard diagnostic system
- Tilt sensor with alarm
- Anti-restart engine protection
- All Motion Alarm
- Horn
- Hour meter
- Safety brackets
- Folding guardrails
- Dual Extended platforms
- European III emission engine
- Flashing Beacon
- Hydraulic oil cooler

## Options

- Automatic leveling hydraulic outriggers
- Hydraulic generator
- Hydraulic welder
- Hydraulic compressor
- Hydraulic water pump
- Overload sensor with alarm
- AC power to platform
- Platform work lights
- Non marking tyre




# DINGLI

## JCPT1523RT

### SELF PROPELLED SCISSOR LIFT - DIESEL



Model  =Engine	JCPT1823RT	JCPT1523RT
<b>Size</b>		
Max. Working Height	18.00m	15.00m
Max. Platform Height	16.00m	13.00m
Overall Height (Rails Up)	3.19m	2.98m
Overall Height (Rails Down)	2.49m	2.28m
Overall Length (With/Without Outriggers)	4.88m/3.98m	
Overall Width	2.27m	
Platform Size (LengthxWidth)	3.98x1.83m	
Platform Extension Size	2.59m	
Ground Clearance (Raised/Stowed)	0.22m	
Wheelbase	2.86m	
Turning Radius (Inside/Outside)	2.35m/5.20m	
Tyres	33x12-20	
<b>Performance</b>		
Max. Occupants	6	7
Gradeability	40%	50%
Up/Down Speed	75/74sec	70/52sec
S.W.L	680kg	
S.W.L On Extension	227kg	
Travel Speed (Stowed)	6.1km/h	
Travel Speed (Raised)	1.1km/h	
Max. Working Slope	2°/3°	
<b>Weight</b>		
Overall Weight (With)	9190kg	8200kg
Overall Weight (Without Outriggers)	8670kg	7680kg
<b>Power</b>		
Diesel Engine Kubota V2403-M-DI	36.5kW/2600rpm	
Diesel Tank	100L	
Hydraulic Tank	130L	
<b>Other Configurations</b>		
4x4 Driving	Self-leveling Hydraulic Outriggers	Slide-out Engine Tray
Dual Extended Platform		

